


SPECIFICATION 210X LC, 220X LC/SLC

STATIC DIMENSIONS



Model		210X LC, 220X LC		220X SLC	
A	Track length on ground	mm	3660		3660
B	Undercarriage overall length	mm	4460		4460
C	Track gauge	mm	2390		2170
D	Width over tracks (500mm trackshoes)	mm	2890		2670
D	Width over tracks (600mm trackshoes)	mm	2990		2770
D	Width over tracks (700mm trackshoes)	mm	3090		2870
D	Width over tracks (800mm trackshoes)	mm	3190		2970
D	Width over tracks (900mm trackshoes)	mm	3290		-
G	Counterweight clearance	mm	1077		1077
H	Tail length	mm	2813		2813
I	Overall width of superstructure	mm	2698		2698
I	Overall width of superstructure (with SIPS)	mm	2828		2828
J	Height over cab	mm	3020		3020
J	Height over XD guard	mm	3120		3120
J	Height over cab (vandal guard – optional)	mm	3330		3330
K	Ground clearance	mm	485		485
L	Track height	mm	885		885
M	Tail swing radius	mm	2846		2846
N	Overall height of upper structure	mm	3170		3170
		Mono		T.A.B	
Dipper lengths		2.4m	3.0m	2.4m	3.0m
E	Transport length	mm	9624	9622	9409
F	Transport height (handrail folded – optional) *	mm	3200	3266	3152
	Transport height (fixed handrail – standard)	mm	3200	3266	3170
				LR	
				6.4m	
					12546
					3079
					3170

ENGINE

Model	JCB 448 DIESELMAX Stage V
Type	4 stroke, 4 cylinder in-line, direct injection, turbocharged diesel.
Rated power (net)	129 kW (173 hp).
Piston displacement	4.8 litres.
Air filtration	Dry element with in cab warning indicator.
Starting system	24 volt.
Batteries	2 x 12 volt.
Alternator	28 volt - 100 ampere.
Maximum torque	690 Nm @ 1500 rpm.
Bore and stroke	106 x 135 mm.

SWING SYSTEM

Swing motor	Axial piston type.
Swing brake	Hydraulic braking plus automatic spring applied disc type parking brake.
Swing torque	68.7 kNm.
Swing speed	11.0 rpm.
Swing gear	Large diameter, internally toothed fully sealed grease bath lubricated.
Swing lock	Switchable brake in cab.

*Excludes FOPS guard / XD FOPS guard.

SPECIFICATION 210X LC, 220X LC/SLC

TRACK DRIVE	
Type	Fully hydrostatic, two speed with autoshift.
Travel motors	Variable swash axial piston type, fully guarded within undercarriage frame.
Final drive	Planetary reduction, bolt-on sprockets.
Service brake	Hydraulic counter balance valve.
Park brake	Disc type, spring applied, automatic hydraulic release.
Gradeability	70% (35°) continuous.
Travel speed	High – 5.7 km/h. Low – 3.2 km/h.
Tractive effort	207.5 kN.

SERVICE CAPACITIES		
Fuel tank	Litres	387
Engine coolant	Litres	38
Engine oil	Litres	20.4
Swing reduction gear	Litres	8
Track reduction gear (each side)	Litres	3.5
Hydraulic system	Litres	250
Hydraulic tank	Litres	120
DEF fluid	Litres	47.7


UNDERCARRIAGE					
Carriage options	LC – Long Carriage, SLC – Standard Long Carriage.				
Construction	Fully welded 'X' frame type with central bellyguarding and sloping sidemembers with dirt relief holes under top rollers.				
Recovery point	Front and rear.				
Upper and lower rollers	Heat treated, sealed and lubricated.				
Track adjustment	Grease cylinder type.				
Track idler	Sealed and lubricated, with spring cushioned recoil.				
Track type	Sealed and lubricated.				
Track shoe options	500mm	600mm	700mm	800mm	900mm
	LC	LC	LC	LC	LC
	SLC	SLC	SLC	SLC	–
	LC, SLC				
No. of upper rollers (per side)	2				
No. of lower rollers (per side)	8				
No. of track guides (per side)	2				
No. of track shoes (per side)	49				

SOUND LEVEL		
Operator Sound Pressure Level – ISO 6396: 2008	67 dB LpA	
Exterior Sound Pressure Level – ISO 6396: 2008 & EU Directive 2000/14/EC	102 dB LwA	

HYDRAULIC SYSTEM	
Pumps	
Main pumps	2 variable displacement axial piston type.
Maximum flow	2 x 228 l/min.
Servo pump	Gear type.
Servo pump maximum flow	16 l/min.
Control valve	
A combined four and five spool control valve with auxiliary service spool as standard.	
Relief valve settings	
Boom/Arm/Bucket	343 bar.
With power boost	373 bar.
Swing circuit	250 bar.
Travel circuit	343 bar.
Pilot control	39 bar.
Filtration	
In tank	105 micron, suction strainer.
Main return line	10 micron, glass fibre element.
Pilot drain line	10 micron, glass fibre element.
Pilot line	10 micron, glass fibre element.
Hydraulic hammer return	10 micron, reinforced microform element.

	Quantity	Bore mm	Rod diameter mm
Boom	2	125	85
Arm	1	130	95
Bucket	1	115	85
LR Bucket	1	95	70
TAB position	1	140	95

OPTIONAL BLADE – 220X LC



A	Blade height	mm	600
B	Blade lift above ground	mm	410
C	Blade cut below ground	mm	440
D	Blade forward of track	mm	567
	Dozer width – 600mm tracks	mm	2990
	Dozer width – 700mm tracks	mm	3110
Additional machine weight with blade			
	600mm tracks	kg	1588
	700mm tracks	kg	1602

SPECIFICATION 210X LC, 220X LC/SLC

BUCKET AND ARM COMBINATION - MONOBOOM															
Bucket options		GP Bucket							HD Bucket						
Bucket width	mm	600	700	900	1100	1200	1350	1500	600	750	900	1100	1200	1350	1500
Bucket capacity	m³	0.38	0.51	0.66	0.81	0.95	1.10	1.25	0.38	0.52	0.66	0.81	0.95	1.11	1.25
Bucket weight	kg	506	565	637	691	763	817	889	544	610	691	752	813	894	955
210X LC															
2.4m Quickhitch (No Quickhitch)		□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)
3.0m Quickhitch (No Quickhitch)		□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	■ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	■ (□)
220X LC															
2.4m Quickhitch (No Quickhitch)		□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)
3.0m Quickhitch (No Quickhitch)		□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	■ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	■ (□)
220X SLC															
2.4m Quickhitch (No Quickhitch)		□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)
3.0m Quickhitch (No Quickhitch)		□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	■ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	□ (□)	■ (□)

□ = Suitable for general excavating materials up to 2000kg/m³.

■ = Suitable for light excavating materials up to 1600kg/m³.

● = Suitable for grading and loading materials up to 1200kg/m³.


These recommendations are given as a guide based on typical operating conditions.
Please contact your distributor for the correct selection of buckets and attachments to suit the application.

WEIGHTS AND GROUND BEARING PRESSURES						
Figures include 1.1m³. bucket 778kg, operator, full fuel tank and 2.4m dipper.						
		500mm shoes	600mm shoes	700mm shoes	800mm shoes	900mm shoes
210X LC Monoboom						
Machine weight	kg	22037	22288	22561	22891	23126
Ground bearing pressure	kg/cm²	0.53	0.44	0.39	0.34	0.31
220X SLC Monoboom						
Machine weight	kg	22730	23002	23275	23605	-
Ground bearing pressure	kg/cm²	0.54	0.46	0.40	0.35	-


WEIGHTS AND GROUND BEARING PRESSURES						
Figures include 1.1m³. bucket 778kg, operator, full fuel tank and 2.4m dipper.						
		500mm shoes	600mm shoes	700mm shoes	800mm shoes	900mm shoes
220X LC Monoboom						
Machine weight	kg	22937	23188	23461	23791	24026
Ground bearing pressure	kg/cm²	0.55	0.46	0.40	0.36	0.32
220X LC T.A.B.						
Machine weight	kg	23653	23905	24177	24508	24743
Ground bearing pressure	kg/cm²	0.57	0.48	0.41	0.37	0.37
220X LC LR						
Machine weight	kg	23461	23712	23985	24315	24550
Ground bearing pressure	kg/cm²	0.56	0.47	0.41	0.36	0.33

SPECIFICATION 210X LC, 220X LC/SLC


WORKING RANGE – MONOBOOM 5.7M				
Dipper length:			2.4m	3.0m
A	Maximum digging reach	mm	9361	9859
B	Maximum digging reach (on ground)	mm	9171	9679
C	Maximum digging depth	mm	6096	6694
D	Maximum digging height	mm	9002	9087
E	Maximum dumping height	mm	6408	6537
F	Maximum vertical wall cut depth	mm	5368	5706
G	Minimum swing radius	mm	3331	2884
H	Minimum dumping height	mm	2906	2306
	Bucket rotation	degrees	183	183
	Maximum dipper tearout	kN	126.6	106.1
	Maximum bucket tearout	kN	150	150



WORKING RANGE – T.A.B. 5.7M				
Dipper length:			2.4m	3.0m
A	Maximum digging reach	mm	9418	9955
B	Maximum digging reach (on ground)	mm	9229	9776
C	Maximum digging depth	mm	5716	6297
D	Maximum digging height	mm	10514	10890
E	Maximum dumping height	mm	7742	8120
F	Maximum vertical wall cut depth	mm	4841	5418
G	Minimum swing radius	mm	2602	2275
H	Minimum dumping height	mm	3683	3008
	Bucket rotation	degrees	183	183
	Maximum dipper tearout	kN	125	103.4
	Maximum bucket tearout	kN	148	148



WORKING RANGE – LR 8.7M			
Dipper length:			6.4m
A	Maximum digging reach	mm	15628
B	Maximum digging reach (on ground)	mm	15514
C	Maximum digging depth	mm	11985
D	Maximum digging height	mm	12710
E	Maximum dumping height	mm	10451
F	Maximum vertical wall cut depth	mm	9307
G	Minimum swing radius	mm	5427
H	Minimum dumping height	mm	1730
	Bucket rotation	degrees	183
	Maximum dipper tearout	kN	68.4
	Maximum bucket tearout	kN	99.8



Working dimensions calculated using 980/B0092 GP bucket on Monoboom and T.A.B. and 980/A0391 GP bucket on LR.

SPECIFICATION 210X LC, 220X LC/SLC

STANDARD/OPTIONAL EQUIPMENT			
ENGINE		CAB & INTERIOR	HYDRAULIC SYSTEM
JCB 448 DIESELMAX Stage V compliant, DOC + SCRF, water cooled diesel turbocharged after cooled electronic 4 cylinder 4.8 litre engine	•	Sound-insulated and 4 dual shock mounted cab	•
Start pre-heat	•	Opening front window and removable lower front window	•
One touch idle	•	Upper door sliding glass in 2 directions	•
Auto-idle function	•	Upper windscreen wiper	•
Automatic engine shutdown	•	4 button joysticks	•
Fan guard	•	Travel pedals and T handle levers	•
Heavy-duty batteries	•	2 foot rests	•
Fuel filter with sedimenter	•	Immobiliser	•
Electronic engine control	•	Loudspeakers and connection for radio	•
Fuel cooler	•	Standard cab filtration	•
Refuelling pump	•	Electric dual tone horn	•
Additional fuel filter with water separator	+	Interior cab light	•
SAFETY		3 x 12v sockets	•
Side guard rails on upper structure and steps	•	7" colour monitor	•
Rear view camera	•	Retractable 2" seat belt	•
Battery isolator	•	Fixed roof glass	•
Key	•	Roof blind	•
Lockable fuel tank cap	•	Cool box	•
Lockable hydraulic tank cap	•	Cup holder	•
Work lights (2 revolving frame, 2 boom mounted)	•	Climate control	•
Roll over protective structure (ROPS)	•	3" seat belt	+
Travel alarm	•	2" hi vis seat belt	+
Additional light options (Levels 2 & 3 available in halogen or LED)	+	3" hi vis seat belt	+
White noise alarm	+	Front, rear and side window blind	•
Demolition cage (FOPS Level II) – XD build only	+	Bluetooth radio (linked to pod controls and screen)	•
Green beacon linked to seat belt	+	Carbon air filter	+
FOPS Level II guard top and front	+	Deluxe seat: Heated, adjustable air suspension seat with adjustable headrest mechanical lumbar support	•
Fire extinguisher (1kg powder)	+	Super deluxe seat: Heated and air ventilation, adjustable air suspension seat with adjustable head rest and electric lumbar support	+
Vandal guards	+	Rain guard visor	+
Chevron counterweight	+	Dual front wiper	+
Rotating roof beacon	+	UNDERCARRIAGE	
2 x counterweight beacons	+	Greased and sealed track links	•
Twin camera	+	Twin track guards	•
360 degree camera	+	Full length track guards	+
Folding handrails	+	500, 600, 700, 800, 900 mm triple grouser shoe	+
Full upper surrounding handrails	+	Dozer for LC carriage 600mm or 700mm tracks	+
Arm limiter	+		

STANDARD •
OPTIONAL +

SPECIFICATION 210X LC, 220X LC/SLC

LIFT CAPACITIES – DIPPER LENGTH: 2.4M, MONOBOOM: 5.7M, TRACKSHOES: 500MM, NO BUCKET											210X LC MONO
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
6m					5400*	5110			5400*	4160	6760
4.5m			6860*	6860*	5860*	4950			5310*	3460	7491
3m			8670*	7180	6650*	4720	5300	3370	4910	3120	7872
1.5m			10210*	6730	7270	4500	5190	3270	4750	3000	7954
0m			10870*	6520	7110	4350	5120	3210	4890	3070	7746
– 1.5m	10960*	10960*	10720*	6490	7060	4310			5400	3370	7223
– 3m	13500*	12880	9770*	6590	7150	4390			6630*	4120	6305
– 4.5m	10130*	10130*	7170*	6890					6590*	6350	4767

LIFT CAPACITIES – DIPPER LENGTH: 3.0M, MONOBOOM: 5.7M, TRACKSHOES: 500MM, NO BUCKET											210X LC MONO
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
7.5m					4670*	4670*			3980*	3980*	6235
6m									3730*	3670	7339
4.5m					5300*	5020	5000*	3490	3690*	3110	8017
3m	12250*	12250*	7800*	7320	6140*	4760	5320	3380	3810*	2820	8374
1.5m			9550*	6780	7030*	4500	5170	3250	4080*	2710	8451
0m	6500*	6500*	10560*	6470	7060	4310	5070	3150	4410	2750	8255
– 1.5m	10820*	10820*	10750*	6360	6970	4220	5030	3120	4790	2980	7767
– 3m	14570*	12540	10170*	6420	7000	4250			5690	3520	6923
– 4.5m	11880*	11880*	8450*	6630					6500*	4920	5562

LIFT CAPACITIES – DIPPER LENGTH: 2.4M, MONOBOOM: 5.7M, TRACKSHOES: 500MM, NO BUCKET											220X LC MONO
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
7.5m									5600*	5600*	5539
6m					5400*	5400*			5400*	4620	6760
4.5m			6860*	6860*	5860*	5490			5310*	3870	7491
3m			8670*	7970	6650*	5260	5780*	3780	5390	3510	7872
1.5m			10210*	7510	7440*	5030	5700	3680	5230	3380	7954
0m			10870*	7300	7800	4890	5630	3610	5380	3460	7746
– 1.5m	10960*	10960*	10720*	7270	7750	4850			5940	3800	7223
– 3m	13500*	13500*	9770*	7370	7160*	4930			6630*	4360	6305
– 4.5m	10130*	10130*	7170*	7170*					6590*	6590*	4767



Lift capacity front and rear.



Lift capacity full circle.

Notes:

1. Lifting capacities are based on ISO 10567, that is: 75% of minimum tipping load or 87% of hydraulic lift capacity, whichever is the less. Lifting capacities marked* are based on hydraulic capacity.
2. Lift capacities assume that the machine is on firm, level ground.
3. Lift capacities may be limited by local regulations. Please refer to your dealer.

SPECIFICATION 210X LC, 220X LC/SLC

LIFT CAPACITIES – DIPPER LENGTH: 3.0M, MONOBOOM: 5.7M, TRACKSHOES: 500MM, NO BUCKET											220X LC MONO
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
7.5m					4670*	4670*			3980*	3980*	6235
6m									3730*	3730*	7339
4.5m					5300*	5300*	5000*	3900	3690*	3480	8017
3m	12250*	12250*	7800*	7800*	6140*	5290	5370*	3780	3810*	3180	8374
1.5m			9550*	7560	7030*	5030	5690	3660	4080*	3060	8451
0m	6500*	6500*	10560*	7250	7690*	4840	5580	3560	4570*	3110	8255
– 1.5m	10820*	10820*	10750*	7150	7660	4760	5540	3520	5280	3370	7767
– 3m	14570*	14000	10170*	7200	7530*	4780			6240*	3970	6923
– 4.5m	11880*	11880*	8450*	7410					6500*	5510	5562

LIFT CAPACITIES – DIPPER LENGTH: 2.4M, T.A.B.: 5.7M, TRACKSHOES: 500MM, NO BUCKET											220X LC T.A.B.
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
9m									7300*	7300*	3459
7.5m			7060*	7060*					5610*	5610*	5628
6m			7300*	7300*	6450*	5690			5110*	4560	6833
4.5m			8350*	8350*	6810*	5520	5460*	3870	4960*	3820	7557
3m			9760*	7960	7390*	5260	5850	3780	5040*	3460	7935
1.5m			10690*	7440	7860*	5010	5730	3670	5190	3330	8016
0m			10660*	7210	7810	4850	5650	3600	5340	3410	7809
– 1.5m	10420*	10420*	9770*	7180	7400*	4800			5580*	3740	7291
– 3m			7950*	7300	5810*				5080*	4540	6383

LIFT CAPACITIES – DIPPER LENGTH: 3.0M, T.A.B.: 5.7M, TRACKSHOES: 500MM, NO BUCKET											220X LC T.A.B.
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
9m			4470*	4470*					4240*	4240*	4568
7.5m					4690*	4690*			3520*	3520*	6364
6m			6070*	6070*	5940*	5820			3260*	3260*	7449
4.5m	8760*	8760*	7640*	7640*	6380*	5620	5480*	3940	3190*	3190*	8118
3m			9130*	8170	7040*	5340	5900	3820	3250*	3140	8470
1.5m			10360*	7570	7640*	5060	5740	3680	3440*	3030	8546
0m	6040*	6040*	10730*	7230	7810	4850	5630	3570	3790*	3080	8353
– 1.5m	10320*	10320*	10210*	7120	7640*	4760	5580	3530	4410*	3320	7871
– 3m	11650*	11650*	8810*	7180	6590*	4790			5040*	3900	7040



Lift capacity front and rear.



Lift capacity full circle.

Notes:

1. Lifting capacities are based on ISO 10567, that is: 75% of minimum tipping load or 87% of hydraulic lift capacity, whichever is the less. Lifting capacities marked* are based on hydraulic capacity.
2. Lift capacities assume that the machine is on firm, level ground.
3. Lift capacities may be limited by local regulations. Please refer to your dealer.

SPECIFICATION 210X LC, 220X LC/SLC

LIFT CAPACITIES – DIPPER LENGTH: 2.4M, MONOBOOM: 5.7M, TRACKSHOES: 500MM, NO BUCKET											220X SLC MONO
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
7.5m									5600*	5600*	5539
6m					5400*	5120			5400*	4190	6760
4.5m			6860*	6860*	5860*	4970			5310*	3500	7491
3m			8670*	7130	6650*	4740	5770	3410	5350	3160	7872
1.5m			10210*	6690	7440*	4520	5660	3320	5190	3050	7954
0m			10870*	6490	7740	4380	5590	3250	5340	3110	7746
– 1.5m	10960*	10960*	10720*	6460	7690	4340			5890	3410	7223
– 3m	13500*	12440	9770*	6560	7160*	4420			6630*	4160	6305
– 4.5m	10130*	10130*	7170*	6850					6590*	6330	4767

LIFT CAPACITIES – DIPPER LENGTH: 3.0M, MONOBOOM: 5.7M, TRACKSHOES: 500MM, NO BUCKET											220X SLC MONO
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
7.5m					4670*	4670*			3980*	3980*	6235
6m									3730*	3710	7339
4.5m					5300*	5030	5000*	3530	3690*	3150	8017
3m	12250*	12250*	7800*	7260	6140*	4770	5370*	3420	3810*	2860	8374
1.5m			9550*	6740	7030*	4520	5640	3290	4080*	2750	8451
0m	6500*	6500*	10560*	6430	7690*	4340	5540	3190	4570*	2800	8255
– 1.5m	10820*	10820*	10750*	6340	7610	4250	5500	3160	5240	3020	7767
– 3m	14570*	12120	10170*	6390	7530*	4280			6210	3560	6923
– 4.5m	11880*	11880*	8450*	6590					6500*	4930	5562

LIFT CAPACITIES – DIPPER LENGTH: 2.4M, MONOBOOM: 5.7M, TRACKSHOES: 600MM, NO BUCKET											220X LC DOZER MONO
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
7.5m									5600*	5600*	5539
6m					5400*	5400*			5400*	4940	6760
4.5m			6860*	6860*	5860*	5860			5310*	4150	7491
3m			8670*	8510	6650*	5630	5780*	4060	5450*	3770	7872
1.5m			10210*	8060	7440*	5410	6120*	3960	5840*	3640	7954
0m			10870*	7850	7940*	5260	6330*	3900	6080	3730	7746
– 1.5m	10960*	10960*	10720*	7820	7960*	5220			6390*	4090	7223
– 3m	13500*	13500*	9770*	7920	7160*	5300			6630*	4980	6305
– 4.5m	10130*	10130*	7170*	7170*					6590*	6590*	4767



Lift capacity front and rear.



Lift capacity full circle.

Notes:

1. Lifting capacities are based on ISO 10567, that is: 75% of minimum tipping load or 87% of hydraulic lift capacity, whichever is the less. Lifting capacities marked* are based on hydraulic capacity.
2. Lift capacities assume that the machine is on firm, level ground.
3. Lift capacities may be limited by local regulations. Please refer to your dealer.

SPECIFICATION 210X LC, 220X LC/SLC

LIFT CAPACITIES – DIPPER LENGTH: 3.0M, MONOBOOM: 5.7M, TRACKSHOES: 600MM, NO BUCKET										220X LC DOZER MONO	
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
7.5m					4670*	4670*			3980*	3980*	6235
6m									3730*	3730*	7339
4.5m					5300*	5300*	5000*	4180	3690*	3690*	8017
3m	12250*	12250*	7800*	7800*	6140*	5660	5370*	4070	3810*	3430	8374
1.5m			9550*	8110	7030*	5400	5820*	3940	4080*	3310	8451
0m	6500*	6500*	10560*	7790	7690*	5220	6160*	3840	4570*	3370	8255
– 1.5m	10820*	10820*	10750*	7690	7920*	5130	6190*	3800	5450*	3640	7767
– 3m	14570*	14570*	10170*	7740	7530*	5160			6240*	4280	6923
– 4.5m	11880*	11880*	8450*	7950					6500*	5920	5562

LIFT CAPACITIES – DIPPER LENGTH: 2.4M, T.A.B.: 5.7M, TRACKSHOES: 600MM, NO BUCKET										220X LC DOZER T.A.B.	
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
9m									7300*	7300*	3459
7.5m			7060*	7060*					5610*	5610*	5628
6m			7300*	7300*	6450*	6070			5110*	4880	6833
4.5m			8350*	8350*	6810*	5900	5460*	4150	4960*	4100	7557
3m			9760*	8500	7390*	5630	6170*	4060	5040*	3720	7935
1.5m			10690*	7990	7860*	5380	6290*	3950	5330*	3590	8016
0m			10660*	7760	7930*	5220	6140*	3880	5770*	3680	7809
– 1.5m	10420*	10420*	9770*	7730	7400*	5180			5580*	4030	7291
– 3m			7950*	7850	5810*	5270			5080*	4880	6383

LIFT CAPACITIES – DIPPER LENGTH: 3.0M, T.A.B.: 5.7M, TRACKSHOES: 600MM, NO BUCKET										220X LC DOZER T.A.B.	
Reach	3m		4.5m		6m		7.5m		Capacity at Max. Reach		
											
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
9m			4470*	4470*					4240*	4240*	4568
7.5m					4690*	4690*			3520*	3520*	6364
6m			6070*	6070*	5940*	5940*			3260*	3260*	7449
4.5m	8760*	8760*	7640*	7640*	6380*	6000	5480*	4220	3190*	3190*	8118
3m			9130*	8710	7040*	5710	5920*	4100	3250*	3250*	8470
1.5m			10360*	8110	7640*	5430	6170*	3960	3440*	3270	8546
0m	6040*	6040*	10730*	7780	7900*	5220	6210*	3850	3790*	3330	8353
– 1.5m	10320*	10320*	10210*	7670	7640*	5130	5800*	3810	4410*	3590	7871
– 3m	11650*	11650*	8810*	7730	6590*	5160			5040*	4210	7040



Lift capacity front and rear.

Notes:

1. Lifting capacities are based on ISO 10567, that is: 75% of minimum tipping load or 87% of hydraulic lift capacity, whichever is the less. Lifting capacities marked* are based on hydraulic capacity.
2. Lift capacities assume that the machine is on firm, level ground.
3. Lift capacities may be limited by local regulations. Please refer to your dealer.



Lift capacity full circle.

SPECIFICATION 210X LC, 220X LC/SLC

LIFT CAPACITIES – DIPPER LENGTH: 6.4M, MONOBOOM: 8.7M, TRACKSHOES: 500MM, NO BUCKET																	220X LC LR MONO		
Reach	3m		4.5m		6m		7.5m		9m		10.5m		12m		13.5m		Capacity at Max. Reach		
																			
Load Point Height	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	kg	mm
11.5m																		1370*	10801
10.5m																		1310*	11627
9m													2020*	1890				1250*	12615
7.5m													2090*	1870				1230*	13363
6m											2220*	2220*	2170*	1820	1860*	1380		1220*	13909
4.5m									2580*	2580*	2410*	2250	2290*	1730	2220*	1340		1240*	14276
3m	8960*	8960*			4090*	4090*	3370*	3370*	2930*	2720	2640*	2090	2450*	1630	2180	1280		1270*	14478
1.5m	3210*	3210*	7070*	6520	4970*	4450	3910*	3260	3280*	2490	2880*	1940	2580	1530	2110	1210		1320*	14523
0m	3290*	3290*	7600*	5730	5710*	3960	4400*	2940	3620*	2280	3040	1800	2480	1440	2050	1150		1410*	14410
– 1.5m	4200*	4200*	7280*	5350	6210*	3640	4700	2710	3640	2110	2920	1680	2390	1360	2000	1110		1520*	14138
– 3m	5350*	5350*	8020*	5210	6280	3470	4540	2570	3520	2000	2830	1600	2340	1310	1980	1090		1680*	13695
– 4.5m	6660*	6660*	8860*	5220	6220	3420	4470	2500	3460	1940	2790	1560	2320	1290				1910*	13066
– 6m	8180*	8180*	8520*	5320	6250	3450	4480	2510	3460	1940	2800	1570	2350	1320				2260*	12220
– 7.5m	9960*	9960*	7900*	5510	6040*	3550	4550	2580	3520	2000	2870	1640						2680	11107
– 9m	9560*	9560*	6900*	5800	5350*	3750	4260*	2720	3390*	2140								3020*	9636
– 10.5m			5280*	5280*	4110*	4060	3110*	3010										3040*	7598



Lift capacity front and rear.



Lift capacity full circle.

Notes:

1. Lifting capacities are based on ISO 10567, that is: 75% of minimum tipping load or 87% of hydraulic lift capacity, whichever is the less. Lifting capacities marked* are based on hydraulic capacity.
2. Lift capacities assume that the machine is on firm, level ground.
3. Lift capacities may be limited by local regulations. Please refer to your dealer.